



# GP MATIC 4T 10W40

Lubricant for 4-Stroke Scooters Engine  
HC-TECH® Technology

## TYPE OF USE

All 4-stroke scooter engines for which manufacturers recommend JASO MB oils.  
Suitable for all types of gasoline fuels, leaded or unleaded, biofuels.

## PERFORMANCES

STANDARDS                      API SN  
SPECIFICATION                JASO MB under N° M065MOT245

MOTUL GP MATIC 4T 10W40 is specially formulated to provide excellent protection for engine. It provides good sludge control and anti-oxidation properties to minimize premature oil ageing. The high temperature resistance property is particularly suitable for city use: full load during long periods and stop and go use with difficult cooling.

JASO MB lubricant ensures optimal scooter performance and fuel economy.

## RECOMMENDATIONS

Drain interval: according to manufacturers' recommendations and to be adjusted according to the using condition. Can be mixed with synthetic or mineral oils.

MOTUL GP MATIC 4T 10W40 should not be used on systems that require JASO MA specification.

## PROPERTIES

Viscosity grade	SAE J 300	<b>10W-40</b>
Density at 20°C (68°F)	ASTM D4052	0.858
Viscosity at 40°C (104°F)	ASTM D445	101.1 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D445	14.2 mm <sup>2</sup> /s
Viscosity Index	ASTM D2270	153
Pour point	ASTM D97	-39°C
Flash point	ASTM D92	238°C
TBN	ASTM D2896	7.1 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - France. Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79. Web Site: [www.motul.com](http://www.motul.com)

09/24