



# GP NEXT 4T 10W40

**Lubricant for 4-Stroke motorcycle engine  
Regenerated Base - Ester**

## TYPE OF USE

GP NEXT 4T 10W40 is a best-in-class 4-stroke motor oil, suitable for all high-performance on- and off-road motorcycles and ATV / UTV / SxS engines. Designed for severe conditions in sport and adventure riding. Meets JASO MA2 specifications for optimal wet clutch performance and engine protection.

GP NEXT is an innovative, sustainable motor oil range featuring:

> A combination of virgin oils and additives, blended with synthetic esters and up to 50% high-end regenerated oils.

> 50% recycled plastic bottles, to reduce plastic waste, decrease carbon footprint and support a more circular economy.

## PERFORMANCES

STANDARDS                      API SP  
SPECIFICATION                JASO MA2 under N° M065MOT287

GP NEXT 4T 10W40 improved oil film resistance at high temperatures for extended overall engine protection especially at high engine speeds, specially formulated for sharp engine response, increased clutch grip / improved shifting, high temperature resistance and protection.

API SP standard guarantees further performance benefits including emissions system compatibility, oxidative stability and deposit control for the most severe modern hardware applications.

JASO MA2 provides the most efficient friction values to ensure best clutch friction engagement in all riding modes.

## RECOMMENDATIONS

Drain interval: according to manufacturers' recommendations and tune to your own use.  
Can be mixed with synthetic or mineral lubricants.

## PROPERTIES

Viscosity grade	SAE J 300	<b>10W-40</b>
Density at 20°C	ASTM D4052	0.856
Viscosity at 40°C	ASTM D445	84.8 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D445	13.4 mm <sup>2</sup> /s
Viscosity Index	ASTM D2270	157
Pour point	ASTM D97	-40°C
Flash point	ASTM D92	239°C
TBN	ASTM D2896	7.2 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - France. BP 94 - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79. Web Site: [www.motul.com](http://www.motul.com)

08/25