



GP POWER 4T 10W30

**Lubricant for 4-Stroke motorcycle engine
HC-TECH® Technology**

TYPE OF USE

Street & road bikes, trails, off-road bikes fitted with 4-stroke engines, integrated gearbox or not, wet or dry clutch, engines with or without catalytic converters.

Other usage: Scooters, ATV, Mopeds...

PERFORMANCES

STANDARDS API SN
SPECIFICATION JASO MA2 under N° M065MOT286

MOTUL GP POWER 4T 10W30 is specially formulated to provide excellent protection for the engine & gearbox. It has high detergent and dispersive properties to provide excellent engine cleanliness and sludge control. The unique additives minimize wear and increase engine and gear lifetime.

JASO MA2 ensures the perfect clutch lock up at start-up, acceleration and full speed, as well as easy gear shifting.

RECOMMENDATIONS

Drain interval: according to manufacturers' recommendations and to be adjusted according to the using condition. Can be mixed with synthetic or mineral lubricants.

PROPERTIES

Viscosity grade	SAE J 300	10W-30
Density at 20°C (68°F)	ASTM D4052	0.867
Viscosity at 40°C (104°F)	ASTM D445	75.5 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	11.3 mm ² /s
Viscosity Index	ASTM D2270	141
Pour point	ASTM D97	-39°C
Flash point	ASTM D92	246°C
TBN	ASTM D2896	7.8 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - France. Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79. Web Site: www.motul.com

08/25