

## GRAISSE 113

Multifunctional Grease

### DESCRIPTION

**GRAISSE 113** is a multi-functional grease for machines working under mild loads and temperatures.

### APPLICATIONS

**GRAISSE 113** is intended for the lubrication of plain bearings, lightly loaded bearings, slideways, sliding blocks, and the lubrication of various machine movements.

**GRAISSE 113** is also suitable for the temporary protection of metal parts and the protection of spray booths.

**GRAISSE 113** meets the following requirements:

- ISO 12924: L-XBBHA2
- DIN 51502: K2G-20

### ADVANTAGES

- Insoluble in cold or tempered water.
- Very easy to inject.
- Good anti-corrosion and anti-wear performances.
- Remains stable at work and when temperature changes.
- Exceptional stickiness performances.

### TECHNICAL INFORMATION

NAME	UNITS	METHOD	GRAISSE 113
Color	-	Visual	Amber
Viscosity at 40°C (104°F)	mm <sup>2</sup> /s	ASTM D7152	114.0
Viscosity at 100°C (212°F)	mm <sup>2</sup> /s	ASTM D7152	8.5
Thickener	-		Calcium Simple
NLGI Grade	-	ASTM D217 mod	2
Drop point	°C	IP 396	>140
Base oil viscosity at 40°C	cSt	ASTM D7152	114.0
Base oil viscosity at 100°C	cSt	ASTM D7152	8.5
Penetration 60 strokes	1/10 mm	DIN 2137	265-295 at 25 °C
Water washout	%	ISO 11009	<10 at 79°C
Temperature range	-		-20°C to +100°C

These characteristics are given only for information and can be updated over time.

**SERVICES AND EQUIPMENT**

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.