INBOARD TECH 4T 10W-40

SYNTHETIC BASE

DESCRIPTION

All recreational and professional 4 stroke engines fitted on boats, along coast or on rivers. Last generation Diesel inboard engines, supercharged, turbocharged or atmospheric, direct injection "Common rail" or "pump injector" type, running with a low/medium sulphur content fuel up to 1%:
BAUDOIN, CATERPILLAR, CUMMINS, IVECO, LOMBARDINI, MERCRUISER, MTU, NANNI, MAN, PERKINS, VETUS-DEUTZ, VOLKSWAGEN, VOLVO PENTA, YAMAHA, YANMAR...
Gasoline Inboard engines : CRUSADER, MERCRUISER, VOLVO PENTA, YAMAHA...
Also suitable for invertors (HURTH, TECHNODRIVE…) according to manufacturer recommendations.

TECHNICAL CHARACTERISTICS

CHARACTERISTICS	METHOD	INBOARD TECH 4T 10W-40
Viscosity grade	SAE J 300	10W-40
Density at 20°C (68°F)	ASTM D1298	0.872
Viscosity at 40°C (104°F)	ASTM D445	101.0 mm²/s
Viscosity at 100°C (212°F)	ASTM D445	14.9 mm²/s
Viscosity Index	ASTM D2270	154.0
Pour point	ASTM D97	-40.0 °C / -40.0 °F
TBN	ASTM D2896	10.0 mg KOH/g
Flash point	ASTM D92	230.0 °C / 446.0 °F

STANDARDS / APPROVALS / PERFORMANCE LEVEL

INBOARD TECH 4T 10W-40 meets the following standards:
- API - CI-4 / CH-4 / SG
- ACEA - E7

INBOARD TECH 4T 10W-40 received approvals from:

- VOLVO - VDS-3

RECOMMENDATIONS

Oil change : According to manufacturers' recommendations ant to be adjusted according to use and oil test results.
Can be mixed with synthetic or mineral oils.

IMPORTANT NOTICE

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment.
The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary. The safety data sheet of this product is available at www.motul.com.