

IRIX HP-SI 180

Greases

DESCRIPTION

IRIX HP-SI-180 is a sprayable, biodegradable grease for points, made from selected biodegradable oils and an inorganic thickener, together with efficient additives, which ensure not only fast bio-degradability but also excellent levels of technical performance, especially in terms of adhesiveness and resistance to washing off.

APPLICATIONS

IRIX HP - SI 180 is a sprayable, biodegradable grease for points which can be used all year round to lubricate the bearings on sets of railway points. It is applied by using a sprayer and spread evenly over the surface to be lubricated. This operating method enables particularly easy, fast application of the product.

Tests carried out on the railway network have shown that the product adheres to the rails very well, even in heavy rain. Furthermore, the product remains highly sprayable, even at very low temperatures; this makes it easy to use in all weathers.

IRIX HP - SI 180 has been approved by the SNCF under the number IPM 02153.

IRIX HP - SI 180 meet the following requirements :

– DIN 51502: KPF2K-30

ADVANTAGES

- Biodegradable.
- Resistance to water.
- Excellent adhesion.

TECHNICAL INFORMATION

NAME	UNITS	METHOD	IRIX HP-SI 180
Color	-	Visual	Dark Yellow
Aspect	-		Gelatinous
Density at 20°C (68°F)	g/mL		0.89
Base oil	-		Microgel
NLGI Grade	-		n/a
Drop point	-		None
Base oil viscosity at 40°C	cSt	ASTM D7152	20.0
Temperature range	-		-30°C to +120°C
Biodegradability	%		> 90 after 21 days in accordance with CEC L-33-A-94
Filterability	-		goes through at 400 µm

These characteristics are given only for information and can be updated over time.

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.