



MI-TECH 5W-40

Gasoline Engine Oil

100% Synthetic

TYPE OF USE

Designed for high performance and provide ultimate level of power especially for recent gasoline engine designs.

Suitable for all turbo or naturally aspirated gasoline engines using leaded or unleaded gasoline, LPG, Autogas fuel. E85 fuel compatible.

All driving conditions: City, Road, Highway.

PERFORMANCE

STANDARDS API SP

Designed to meet API SP specifications. Provides exceptional engine protection and greater power when compared to more viscous products.

The high performance anti-wear additive results in reduction of engine internal frictions and increases engine life duration by reducing wear.

Excellent anti-oxidation preventing premature oil thickening and ageing due to thermal stress. Very efficient anti-deposit and anti-black sludge power which maintains a clean engine. Anti-corrosion, Anti-foam properties.

RECOMENDATIONS

Drain period: according to manufacturers' recommendations and driving patterns.

PROPERTIES

Viscosity grade	SAE J 300	5W-40
Density at 20°C	ASTM D4052	0.845
Viscosity at 40°C	ASTM D445	92.1 mm²/s
Viscosity at 100°C	ASTM D445	14.6 mm²/s
Viscosity index	ASTM D2270	166
Pour point	ASTM D97	-36°C
Flash point	ASTM D92	226°C
TBN	ASTM D2896	7.0 mg KOH/g