



MOTO 4T 20W40

**Lubricant for 4-Stroke Motorcycle Engine
Urban & Utility
Mineral**

TYPE OF USE

All 4-stroke motorbikes.

PERFORMANCES

STANDARDS	API SL
SPECIFICATION	JASO MA2 under N° M065MOT273

Good lubricating properties which decrease friction and wear for engine, gear and clutch protection for everyday use.

Strong dispersant and detergent properties to ensure engine cleanliness and deposit control.

Excellent shear resistance and oil film thickness to protect gears and ensure engine durability.

JASO MA2 ensures the perfect clutch lock up at start-up, acceleration and full speed.

Easy gear shifting.

RECOMMENDATIONS

Oil change: follow the manufacturers' recommendations and to be adjusted according to use condition.
Can be mixed with synthetic or semi synthetic lubricants.

PROPERTIES

Viscosity grade	SAE J 300	20W-40
Density at 20°C (68°F)	ASTM D4052	0.874
Viscosity at 40°C (104°F)	ASTM D445	130.6 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	14.4 mm ² /s
Viscosity Index	ASTM D2270	110
Pour point	ASTM D97	-30°C
Flash point	ASTM D92	276°C
TBN	ASTM D2896	5.6 mg KOH/g