



# MOTO 4T 20W40

**Lubricant for 4-Stroke Motorcycle Engine  
Urban & Utility  
Mineral**

## TYPE OF USE

All 4-stroke motorbikes.

## PERFORMANCES

STANDARDS                      API SL  
SPECIFICATION                JASO MA2 under N° M065MOT293

Good lubricating properties which decrease friction and wear for engine, gear and clutch protection for everyday use.

Strong dispersant and detergent properties to ensure engine cleanliness and deposit control.  
Excellent shear resistance and oil film thickness to protect gears and ensure engine durability.

JASO MA2 ensures the perfect clutch lock up at start-up, acceleration and full speed.  
Easy gear shifting.

## RECOMMENDATIONS

Oil change: follow the manufacturers' recommendations and to be adjusted according to use condition.  
Can be mixed with synthetic or semi synthetic lubricants.

## PROPERTIES

|                            |            |                          |
|----------------------------|------------|--------------------------|
| Viscosity grade            | SAE J 300  | <b>20W-40</b>            |
| Density at 20°C (68°F)     | ASTM D4052 | 0.871                    |
| Viscosity at 40°C (104°F)  | ASTM D445  | 132.6 mm <sup>2</sup> /s |
| Viscosity at 100°C (212°F) | ASTM D445  | 14.4 mm <sup>2</sup> /s  |
| Viscosity Index            | ASTM D2270 | 108                      |
| Pour point                 | ASTM D97   | -30°C                    |
| Flash point                | ASTM D92   | 250°C                    |
| TBN                        | ASTM D2896 | 6.4 mg KOH/g             |

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - France. Tel : 33 1 48 11 70 00 - Fax : 33 1 48 33 28 79. Web Site : [www.motul.com](http://www.motul.com)

08/25