

MOTUL CRESSIDA SAE 40

Mineral

DESCRIPTION

MOTUL CRESSIDA SAE 40 is a high performance mineral engine oil dedicated to the latest generation of 4-stroke engines running with biogas or landfill gas and requiring low ash oil.

MOTUL CRESSIDA SAE 40 high quality base oil provides superior valve recession protection in order to reduce nitration phenomena. The additive system reduces sludge deposit and plug fouling leading to increased spark plug life enabling longer operating life and lowering maintenance costs.

APPLICATIONS

MOTUL CRESSIDA SAE 40 is a high performance landfill gas and biogas engine oil for latest generation 4-stroke, spark-ignition stationary gas engines.

ADVANTAGES

- Reduced valve wear.
- Very low piston deposit and sludge formation.
- Extended spark plugs life.
- Optimized drain interval and lifecycle cost.
- Low maintenance costs.

TECHNICAL CHARACTERISTICS

CHARACTERISTICS	METHOD	MOTUL CRESSIDA SAE 40
Viscosity grade	SAE J 300	40
Density at 20°C (68°F)	ASTM D1298	0.87 cSt
Viscosity at 40°C (104°F)	ASTM D445	118.0 cSt
Viscosity at 100°C (212°F)	ASTM D445	13.5 cSt
Pour point	ASTM D97	-24.0 °C
Sulfated Ash	ASTM D874	0.50 % weight
TBN	ASTM D2896	4.5 mg KOH/g
Flash point	ASTM D92	246.0 °C

STANDARDS / APPROVALS / PERFORMANCE LEVEL

MOTUL CRESSIDA SAE 40 received approvals from:

- MAN - M3271-4 (Engine oil for stationary engine - Biogas)
- MWM - TCG (Gas engines)
- CATERPILLAR - CG (Gas engines)

MOTUL CRESSIDA SAE 40 meets or exceeds the most common specifications and OEM requirements:

- GE JENBACHER - Type 2 (Class B and C gas engines)
- GE JENBACHER - Type 3 (Class B and C gas engines)
- GE JENBACHER - Type 4 (Class B and C gas engines)
- GE JENBACHER - Type 6 (Class B and C gas engines)
- CATERPILLAR - G3520 C Engines

IMPORTANT NOTICE

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment. The safety data sheet is available on www.motul.com.

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary.