



MULTIPOWER D-TURBO 15W-40

Diesel Engine Lubricant

Technosynthese®

TYPE OF USE

Technosynthese® lubricant specially designed for cars powered by diesel engines, including those fitted with EGR systems.

Suitable for use in larger engines such as Sports Utility Vehicles (SUV), light-duty trucks, vans and passenger cars requiring a 15W40 viscosity grade and API CK-4 engine oil.

Can also be used in gasoline engines requiring API SN oils.

PERFORMANCE

PERFORMANCE API CK-4 / SN

MULTIPOWER D-TURBO provides high level of protection and prolongs the engine life. Thanks to its powerful soot handling performance to control oil thickening, preventing harmful deposit and wear. Outstanding anti-wear and anti-oxidation properties for a perfect engine condition. Good oil evaporation rate for lower oil consumption.

RECOMENDATIONS

Drain interval: according to manufacturers' recommendations and tuned to your own use.
Can be mixed with synthetic or mineral oils.

PROPERTIES

Viscosity grade	SAE J 300	15W-40
Density at 20°C (68°F)	ASTM D4052	0.867
Viscosity at 40°C (104°F)	ASTM D445	108.5 mm²/s
Viscosity at 100°C (212°F)	ASTM D445	14.8 mm²/s
Viscosity index	ASTM D2270	141
TBN	ASTM D2896	8.4 mg KOH/g