



NISMO COMPETITION OIL 2189E 75W-140



Lubricant for limited slip differentials
100% Synthetic – Ester

TYPE OF USE

Recommended by NISSAN and NISMO for the Nissan GT-R R35's front and rear differentials.
Lubricant for hypoid differentials with limited slip system operating under harsh conditions, involving heavy loads and high speeds.

Other applications: Racing car, Drifting car, Tuning car.

PERFORMANCES

STANDARDS

API GL-5

APPROVALS

NISMO Nissan Motorsport International

PERFORMANCES

NISMO WARRANTY can apply on the GT-R R35

100% Synthetic - Ester based Extreme Pressure lubricant for an efficient anti wear protection, a better resistance at high temperature and a longer lifetime.

Proprietary friction modifiers cater unparalleled limited slip differential stability, preventing chatter/ judder that affect driveability.

0% Shear loss: Unshearable oil film in extreme conditions, that guarantees a very high lubricating power which decreases friction and wear.

140 viscosity grade at high temperature to provide outstanding oil film resistance.

Superlative antioxidation properties, to retard oil degradation at high temperatures.

Anti-corrosion, Anti-foam.

RECOMMENDATIONS

Type 2189E (75W-140) is appointed as NISSAN genuine differential oil for the NISSAN GT-R (R35) 2012 and onward.

This oil is also specified as a "vehicle under warranty" applicable differential oil for models prior to 2012.

Under normal driving conditions, change differential oil every 6,000 miles (10,000 km) or 6 months, whichever comes first.

When the oil temperature reaches between 248°F (120°C) and 284°F (140°C) while driving, change differential oil every

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com



NISMO COMPETITION OIL 2189E 75W-140



Lubricant for limited slip differentials
100% Synthetic – Ester

3,000 miles (5,000 km).

Under race track conditions, change the differential oil every 1,850 miles (3,000 km).

Do not mix with other lubricants.

PROPERTIES

| | | |
|----------------------------|------------|--------------------------|
| Color | Visual | Amber |
| Viscosity grade | SAE J 306 | 75W-140 |
| Density at 20°C (68°F) | ASTM D1298 | 0.876 |
| Viscosity at 40°C (104°F) | ASTM D445 | 199.7 mm ² /s |
| Viscosity at 100°C (212°F) | ASTM D445 | 29.7 mm ² /s |
| Viscosity Index | ASTM D2270 | 189.0 |
| Pour point | ASTM D97 | -45.0 °C / -49.0 °F |
| Flash point | ASTM D92 | 212.0 °C / 414.0 °F |

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br\>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com