



# OUTBOARD TECH 4T 10W40

**Lubricant for Marine 4-stroke Engines  
Gasoline engines**

**Technosynthese®**

## TYPE OF USE

Technosynthese® lubricant reinforced with synthetic base stocks specially designed for use in marine gasoline 4 stroke engines running in severe conditions, calling for NMMA FC-W lubricants, outboard and sterndrive from: BOMBARDIER, HONDA, MARINER, MERCURY, SELVA, SUZUKI, TOHATSU, YAMAHA...

## PERFORMANCE

STANDARDS            API SL  
APPROVALS            NMMA FC-W under n° FB-14800W

FC-W standard, specially developed for lubricant intended for use in marine engines, is more stringent than requirements for standard marine oils on following points:

- Higher HTHS viscosity at 150°C to ensure better oil film resistance at high temperature and absorb fuel dilution produced during long idling period.
- 40 grade viscosity at high temperature for severe conditions and warm climates.
- Better shear resistance to maintain lubricant performance at high temperature.
- Outstanding anti-corrosion properties to avoid corrosion due to sea water or salt water fog that can reach combustion chamber through exhaust pipe. Better anti-corrosion performance during wintering periods.
- Keep lubricant original properties even contaminated by sea water.
- Better oxidation resistance
- Anti-foam properties to avoid foaming and air bubbles introduction into oil circuit.
- Anti-clogging properties to protect oil filters.

## RECOMMENDATIONS

Drain interval: according to manufacturers' recommendations and tune to your own use.  
Can be mixed with synthetic or mineral oils

## PROPERTIES

Viscosity grade	SAE J 300	<b>10W-40</b>
Density at 20°C (68°F)	ASTM D1298	0.861
Viscosity at 40°C (104°F)	ASTM D445	93.9 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D445	14.0 mm <sup>2</sup> /s
Viscosity Index	ASTM D2270	152
Pour point	ASTM D97	-36°C
Flash point	ASTM D92	228°C
TBN	ASTM D2896	7.1 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - France. Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79. Web Site: [www.motul.com](http://www.motul.com)

02/25