

RUBRIC AW 22

Hydraulic Fluids

DESCRIPTION

RUBRIC AW 22 is a hydraulic, circulating, slushing and anti-oxidation oil.

APPLICATIONS

RUBRIC AW 22 is an anti-corrosive and anti-oxidative hydraulic and circulating oil.

RUBRIC AW 22 meets the following requirements:

- ISO 11158 categories HL
- ISO 6743-4 category HL
- DIN 51524 part 1 HL
- NF E 48603 HL

ADVANTAGES

- Excellent resistance to oxidation.
- Excellent protection against corrosion.
- Good hydrolysis stability.
- Excellent desemulsification.
- Excellent thermal stability.

TECHNICAL INFORMATION

NAME	UNITS	METHOD	RUBRIC AW 22
Density at 20°C (68°F)	-	ISO 12.185	0.851
Viscosity at 40°C (104°F)	cSt	ASTM D445	22.0
Viscosity at 100°C (212°F)	cSt	ASTM D445	4.4
Viscosity Index	-	ASTM D2270	109.0
Flash point	°C	ASTM D92	212.0
Pour point	°C	ASTM D97	-28.0

These characteristics are given only for information and can be updated over time.

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.