

RUBRIC B 46

Hydraulic Fluids

DESCRIPTION

RUBRIC B 46 is a hydraulic, circulating, slushing and anti-oxidation oils.

APPLICATIONS

RUBRIC B 46 is an anti-corrosive and anti-oxidative hydraulic and circulating oil.

RUBRIC B 46 meets the following requirements:

- ISO 11158 categories HL
- ISO 6743-4 category HL
- DIN 51524 part 1 HL
- NF E 48603 HL

ADVANTAGES

- Excellent resistance to oxidation.
- Excellent protection against corrosion.
- Good hydrolysis stability.
- Excellent desemulsification.
- Excellent thermal stability.

TECHNICAL INFORMATION

NAME	UNITS	METHOD	RUBRIC B 46
Density at 20°C (68°F)	-	ISO 12.185	0.878
Viscosity at 40°C (104°F)	cSt		46.0
Viscosity at 100°C (212°F)	cSt		6.7
Viscosity Index	-		100.0
Flash point	°C		218.0
Pour point	°C		-33.0

These characteristics are given only for information and can be updated over time.

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.