

RUBRIC EE 150

Hydraulic Fluids

DESCRIPTION

RUBRIC EE 150 is a hydraulic, circulating, slushing and anti-oxidation oils.

APPLICATIONS

RUBRIC EE 150 is an anti-corrosive and anti-oxidative hydraulic and circulating oil.

RUBRIC EE 150 meets the following requirements:

- ISO 11158 categories HL
- ISO 6743-4 category HL
- DIN 51524 part 1 HL
- NF E 48603 HL

ADVANTAGES

- Excellent resistance to oxidation.
- Excellent protection against corrosion.
- Good hydrolysis stability.
- Excellent desemulsification.
- Excellent thermal stability.

TECHNICAL INFORMATION

NAME	UNITS	METHOD	RUBRIC EE 150
Density at 20°C (68°F)	-	ISO 12.185	0.887
Viscosity at 40°C (104°F)	cSt	ASTM D445	150.0
Viscosity at 100°C (212°F)	cSt	ASTM D445	14.4
Viscosity Index	-	ASTM D2270	98.0
Flash point	°C	ASTM D92	198.0
Pour point	°C	ASTM D97	-15.0

These characteristics are given only for information and can be updated over time.

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.