

RUBRIC HLPD 46

Hydraulic Fluid

DESCRIPTION

RUBRIC HLPD 46 is a hydraulic fluid based on mineral oil with detergent and dispersant qualities.

Its anti-wear and zinc-free (ashless) technology deliver reliable performance and ultimate cleanliness in applications contaminated by aqueous products such as metalworking fluids.

APPLICATIONS

RUBRIC HLPD 46 hydraulic fluid is suitable for a wide range of industrial and manufacturing applications where a high level of dispersancy is required due to water ingress or contamination.

RUBRIC HLPD 46 oil is particularly recommended for use in hydraulic systems of machine tools, where water mixed cutting fluids may enter the hydraulic system.

RUBRIC HLPD 46 fulfils the most common specifications and OEM requirements:

- DIN 51524 part 2 (HLP)
- Daimler Chrysler DBL 6721
- Ortlinghaus test for wet running clutch-brake-units according to ON 9.2.19.

ADVANTAGES

- Superior emulsification properties.
- Excellent anti-wear properties.
- Excellent foaming tendency and stability control.
- Rapid air release.
- Very good oxidation stability.
- Superior filterability.

**TECHNICAL INFORMATION**

TECHNICAL CHARACTERISTICS	UNITS	METHOD	RUBRIC HLPD 46
Color	-	Visual	Light Yellow
Viscosity at 40°C (104°F)	mm ² /s	ASTM D445	46.0
Viscosity at 100°C (212°F)	mm ² /s	ASTM D445	7.2
Viscosity Index	-	ASTM D2270	115.0
Flash point	°C	ASTM D92	238.0
Pour point	°C	ASTM D97	-33.0
Foam, Seq I, II, III	ml/ml	NFT 60 129	0/0-10/0-0/0
4 Ball test - Wear scar	mm	ISO 20.623	0.49
4 Ball test - Weld load	kg	ISO 20.623	240

These characteristics are given only for information and can be updated over time.

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.