

## SAFCO KLEEN VF 200

Degreasing Agent

### DESCRIPTION

**SAFCO KLEEN VF 200** is a technical fluid specifically developed to replace petroleum and chlorinated solvents in their applications to cold or hot surface.

Useful product for cleaning applications :

- Surface does not need to be completely dry after cleaning
- Requires a stronger solvent power compared to hydrocarbon based solvents (elimination of resin deposit inks)
- Forms a temporary protective film on the treated parts.

### APPLICATIONS

**SAFCO KLEEN VF 200** is a technical fluid specifically developed to replace petroleum and chlorinated solvents in their application to cold or hot surfaces. It is used non diluted, cold or warm (80°C max).

Can be applied with cloth, in a cleaning fountain, can be sprayed or dipped.

**SAFCO KLEEN VF 200** is a strong degreasing fluid suitable for sensitive materials and confined environments.

It is well-suited for the cleaning or degreasing of mechanical parts or machining fluid residues.

### ADVANTAGES

- Strong degreasing power.
- Non-flammable, with a flash point over 170 °C, it avoids any ATEX risks.
- Compatible with the most materials, metals, plastics, elastomers, rubber, painted surfaces.
- Can be used in closed spaces.

**TECHNICAL INFORMATION**

TECHNICAL CHARACTERISTICS	UNITS	METHOD	SAFCO KLEEN VF 200
Aspect	-		Clear
Density at 20°C (68°F)	-	ISO 12185	0.874
Viscosity at 40°C (104°F)	mm <sup>2</sup> /s	ISO 3104	4.5
Flash point	°C	ISO 2719	>170 (closed up)
Freezing point	°C	ASTM D97	-6.0
Copper Strip Corrosion	-	NTF M 07105	1a
Evaporation	min	NF T 30 301	does not evaporate
KB Value	-	ASTM D1133	100.0
Vapour Pressure	mbar	NF M 07 007	< 0.1 (REID at 20°C)

These characteristics are given only for information and can be updated over time.

**HEALTH & SAFETY**

- VOC-free
- Non toxic
- Without solvent
- 100 % Biodegradable
- No odor
- No irritating

**SERVICES AND EQUIPMENT**

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.