

## SAFCO SPRAY 21

Degreasing Agent

### DESCRIPTION

**SAFCO SPRAY 21** is an excellent degreasing solvent specifically developed for surface cleaning and preparation processes in the presence of considerable levels of pollution. It is also well-suited for the removal of ink, oil and grease.

**SAFCO SPRAY 21** has a high purity index and is suitable for cleaning polluted electrical equipment. It has no effect on most high density plastics and elastomers.

**SAFCO SPRAY 21** is an aerosol. For a 25L jerrycan or a 200L drum need, the **SAFCO KLEEN 21** cleaner is available.

### APPLICATIONS

**SAFCO SPRAY 21** can be used in plastic injection, mechanical engineering, maintenance workshops, precision engineering, aeronautics, electrical and electronic equipment industrial areas for the following applications :

#### Degreasing of mechanical and plastic parts

Excellent solvent for oil, grease and temporary protective products. Compatible with most plastics and elastomers, as well as metals, including plating or precious metals.

#### Cleaning off excess glue or resin

Very good diluent for most organic substances. Good solvent for glues, UV adhesives, plastics and non-reticulated resins.

#### Surface preparation prior to bonding or painting

Can be used to clean parts made of metal, certain plastics, composites and elastomers. Can be used to remove organic or inorganic pollution prior to surface treatment.

#### Brake and clutch cleaner

Excellent solvent for brake fluids, sludge, encrusted duct and metallic residues. Evaporation rate adapted to allow the cleaning agent to pene-


### ADVANTAGES

- Compatible with most plastics and elastomers.
- Quick evaporation time.
- Cleans part from oil, grease, ink, glue, resins or plastics residues.

trate the entire braking system and to completely dissolve dust and dirt. Leaves no residue.

### Maintenance in food processing environments

Product complies to US FDA and CFR 21 regulations, and with NSF standards. Can be used in food processing industries to clean and degrease all packaging and handling equipment.



### TECHNICAL INFORMATION

TECHNICAL CHARACTERISTICS	UNITS	METHOD	SAFCO SPRAY 21
Aspect	-		Clear
Density at 20°C (68°F)	-	ISO 12185	750
Self-Ignition Point	°C	ASTM E 659	250.0
Flash point	°C	NF EN 22719	23 (closed cup)
Freezing point	°C	ISO 3016	-30.0
Copper Strip Corrosion	-	NTF M 07105	1a
Evaporation	min	NF T 30 301	10.0 at 25 °C
KB Value	-	ASTM D1133	90.0

These characteristics are given only for information and can be updated over time.

### PACKAGING

650 mL Aerosol – pack of 6

### INSTRUCTIONS

Considering the wide range of substrates used in industries, we recommend that users conduct compatibility tests with sensitive materials to degrease. These compatibilities often depend on operating procedures and therefore also on the contact time between **SAFCO SPRAY 21** and plastic materials.

- Aerosol under pressure. Protect against sunlight and do not expose to temperatures exceeding 50 ° C.
- Do not pierce or burn even after use.
- Do not spray on a flame or incandescent material.
- Keep out from children.
- Keep away from flames and sources of ignition – Do not smoke.
- Don't use in vapor phase.
- Avoid any projection on clothe.
- Do not discharge into drains after use. Use in a ventilated area.



## SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.