

SAFCO SPRAY MULTILUBE

Lubrication / Maintenance

DESCRIPTION

10 PURPOSES AEROSOL 10, BIODEGRADABLE AND NO VOC CONTENT

Penetrating, deoxidizing, anti-humidity, lubricant, degreaser, tar remover, scrubbing, inks thinner, anti-resin, cleaner for plasters and mastics.

- Clean, colorless, it is guaranteed silicon and orthophosphoric acid free and contains no chlorinated solvents
- Remove scrubbing, eliminates light or heavy hydrocarbons
- Based on natural plant esters
- No photochemical reactivity
- Non irritating product
- Very low surface tension
- Compatible with all plastic materials and elastomers and do not attack paint

APPLICATIONS

Nuts and bolts, hinges, pins, machine-tool slides degumming, axes, sheathed cables, electromechanical contacts, hinges, guides, columns, rails, telescopic antennas, chains degreasing.

ADVANTAGES

- One product for various applications.
- Biodegradable.
- Economical.
- Better corrosion protection.
- Anti-wear.
- Without silicone, acids or chlorinated solvents.
- Compatible with all plastics, elastomers and paint.

TECHNICAL INFORMATION

TECHNICAL CHARACTERISTICS	UNITS	METHOD	SAFCO LUBE	SPRAY	MULTI-
Color	-	Visual	Amber		
Aspect	-		Clear		
Density at 20°C (68°F)	-	ISO 12185	0.837		
Viscosity at 40°C (104°F)	mm ² /s	ISO 3104	3.3		
Flash point	°C	NF EN 22719	>100 (closed cup)		
Boiling point	°C		240.0		
Vapour Pressure	hPa		< 0.1		

These characteristics are given only for information and can be updated over time.

PACKAGING

650 mL Aerosol – pack of 6

INSTRUCTIONS

Aerosol under pressure. Protect against sunlight and do not expose to temperatures exceeding 50 ° C.

- Do not pierce or burn even after use.
- Do not spray on a flame or incandescent material.
- Keep out from children.
- Keep away from flames and sources of ignition – Do not smoke.
- Shake before use.
- Temperature of use: -10 to 220°C

To install the nozzle fitted with an extension, remove the current nozzle well in the axis of the can; do not make lateral movements so as not to damage the seal of the valve. Aerosol usable in all positions.

It is essential to consult the safety data sheet before using this product. Remove all ignition points while the product is in use, and in particular avoid using the product on an incandescent body or on a hot surface. Do not use during vapor phase. Avoid all splashing onto cloth to avoid wicking. No smoking. Do not allow the product to leak into the mains drainage system after use. Use in a well-ventilated space.

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.