

SCOOTER EXPERT 2T**Lubricant for 2 Stroke Scooter engines
Technosynthese® – Anti-Smoke****TYPE OF USE**

All scooters daily used in town/city conditions.
Suitable for 2 Stroke engines, direct injection or conventional carburetor.
Can be used with oil injection systems or in premix.
Suitable for all type of gasoline fuels, leaded or unleaded, with or without Ethanol, biofuels.
Compatible with catalytic converters.

PERFORMANCES

STANDARDS	API TC ISO -L-EGC
PERFORMANCES	JALOS FD under N° 033MOT071

Synthetic Technosynthese® engine oil developed for scooter 2 Stroke engines running at high rpm.
Reinforced with synthetic base stocks for outstanding oil film resistance and anti-wear protection.
Avoid deposits and ensures engine cleanliness at all levels: combustion chamber, spark plug, piston top, ring grooves, exhaust port, exhaust pipe...etc.

RECOMMENDATIONS

Mixing ratio: from 2% to 4% (from 50:1 to 25:1) according to manufacturers' requirements.
To be adjusted according to your own use.

PROPERTIES

Color	Visual	Green
Density at 20°C (68°F)	ASTM D1298	0.857

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com



SCOOTER EXPERT 2T

Lubricant for 2 Stroke Scooter engines
Technosynthese® – Anti-Smoke

Viscosity at 40°C (104°F)	ASTM D445	65.2 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	9.8 mm ² /s
Viscosity Index	ASTM D2270	133.0
TBN	ASTM D2896	1.0 mg KOH/g
Flash point	ASTM D92	144.0 °C / 291.0 °F