

**SCOOTER GEAR 85W-140****Transmission oil – Extreme Pressure****Mineral****TYPE OF USE**

Specially designed for the heavy loaded working conditions of scooter and moped transmissions. Adapted packaging size for easy use.

Especially recommended for transmissions of SYM scooters, MOTO GUZZI final drives but also any other transmission or gearbox that requires an SAE 85W-140 viscosity grade oil.

**PERFORMANCES****STANDARDS**                      **API GL-4 / GL-5**

Very high lubricating power to withstand successive full speed start-ups and stops in city driving conditions.  
140 grade at hot temperature to provide outstanding oil film resistance at hot temperature and/or to reduce transmission noise. Oil film thickness remains very stable in various driving conditions, idle, sharp acceleration, and full power.  
Extreme Pressure and anti-wear additives to increase gear set lifetime operating under very high revolutions (gear reduction) and shocks during riding (rear wheel lock-up).  
Excellent anti-corrosion, anti-oxidation and anti-foam power.

**RECOMMENDATIONS**

Oil change: According to manufacturers' requirements and to be adjusted according to your own use.



## SCOOTER GEAR 85W-140

Transmission oil – Extreme Pressure

Mineral

### PROPERTIES

Viscosity grade	SAE J 306	85W-140
Density at 20°C (68°F)		0.904
Viscosity at 40°C (104°F)		355.0 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)		25.0 mm <sup>2</sup> /s
Viscosity Index		100.0
Pour point		-19.0 °C / -2.0 °F
Flash point		208.0 °C / 406.0 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

08/21