

SCOOT 4T 5W40 MA DE**4 Stroke engine oil Scooters and Maxi Scooters
Synthese-Technologie – JASO MA****TYPE OF USE**

Specifically designed for powerful and recent scooters and maxi-scooters fitted with 4 stroke engines, any engine displacement, with or without catalytic converters, with integrated gearbox and wet clutch.

All scooters used for daily commuting and urban riding.

Suitable for all type of gasoline fuel, leaded or unleaded, with or without Ethanol, biofuels.

PERFORMANCES

STANDARDS API SN / SM / SL / SJ

PERFORMANCES JALOS MA under N° M033MOT171

Synthese-Technologie engine oil, reduces engine internal friction, improves mechanical efficiency.

The JASO MA approval offers an excellent friction levels to guarantee clutch response and durability.

Improved oil resistance for excellent high temperature protection particularly indicated for city use: full load during long periods and stop & go use with difficult cooling.

The SAE 5W-40 viscosity grade corresponds to the most recent manufacturers' recommendations and improves engine starts when cold and therefore reduces wear.

Very low volatility to reduce oil consumption.

Ensures engine cleanliness, detergent and dispersant properties, and resistance to viscosity increase from unburned deposits produced by the engine. High ageing resistance.

Anti-oxidation, Anti-corrosion, Anti-foam properties.

RECOMMENDATIONS

Drain interval: refer to manufacturers' recommendations and tune to your own use.

Can be mixed with synthetic or mineral oils.



SCOOT 4T 5W40 MA DE

**4 Stroke engine oil Scooters and Maxi Scooters
Synthese-Technologie – JASO MA**

PROPERTIES

Viscosity grade	SAE J 300	5W-40
Density at 20°C (68°F)	ASTM D1298	0.850
Viscosity at 40°C (104°F)	ASTM D445	85.3 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	14.1 mm ² /s
Viscosity Index	ASTM D2270	170.0
Pour point	ASTM D97	-35.0 °C / -31.0 °F
TBN	ASTM D2896	10.1 mg KOH/g
Flash point	ASTM D92	227.0 °C / 441.0 °F