



SNOWPOWER 4T 0W-40

Snowmobile 4-Stroke Engine Lubricant

100% Synthetic – Ester

TYPE OF USE

Specially designed for high performance snowmobiles 4-Stroke engines: Yamaha, Ski-doo/ BRP, Artic Cat, Lynx...

Strongly recommended for racing use.

Also compatible for ATV and UTV.

Suitable for all types of Gasoline: leaded or unleaded, winter or regular fuels, biofuels.

Compatible with catalytic converters.

PERFORMANCE

STANDARDS API SN / SM / SL

PERFORMANCES JASO MA2

This 100% Synthetic - Ester engine oil is formulated and developed to meet the most stringent requirements of very powerful engines operating in polar extreme conditions:

- Faster rev raisings and maximum power output.
- Outstanding engine protection at high rpm and high temperature.
- Balanced engine operating temperature.
- Easy start up in polar cold.
- Avoid starter clutch sliding.

RECOMMENDATION

Drain interval: refer to manufacturers' recommendations and tune to your own use.

MOTUL SNOWPOWER 4T 0W-40 can be mixed with synthetic or mineral oils.

PROPERTIES

Viscosity grade	SAE J 300	0W-40
Density at 20°C (68°F)	ASTM D4052	0.860
Viscosity at 40°C (104°F)	ASTM D445	87.7 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	14.7 mm ² /s
Viscosity index	ASTM D2270	176
Pour point	ASTM D97	-48°C
Flash point	ASTM D92	232°C
TBN	ASTM D2896	10.1 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 – Web Site: www.motul.com

10/24