

# **MOTUL SPECIFIC 0720 5W-30**



Lubricant for RENAULT Diesel engines with DPF Synthese-Technologie

## TYPE OF USE

Specifically designed for the latest generation of Diesel engines with diesel particulate filter (DPF) from RENAULT group (Renault, Dacia, Samsung) requiring an approved Renault RN0720 oil, and meeting Euro 4, 5 or 6 emissions level

For the 2.2L dCi with DPF engines, use only Renault RN0710 approved product such as MOTUL 8100 X-clean 5W-40, MOTUL 8100 X-cess 5W-40 or MOTUL 6100 Synergie+ 10W-40.

Renault RN0720 standard applies also to the vehicles RENAULT Laguna III 1.5L dCi without DPF built before October 2008 and RENAULT Kangoo II 1.5L dCi without DPF built before June 2008.

If in doubt, before use always refer to the vehicle owner's manual.

### **PERFORMANCES**

STANDARDS ACEA C4

APPROVALS RENAULT RN0720 under N° RN0720-08-005

PERFORMANCES MERCEDES-BENZ MB 226.51, FIAT 9.55535-S4

RENAULT has developed RN0720 standard for oils able to endure the most severe thermal constrains along with modern after treatment systems compatibility.

The very low Sulfated Ash level and reduced Sulfur and Phosphorous contains (Low SAPS) technology protect and extend lifetime of after treatment systems (DPF).

The 100% Synthetic base stock provides a high thermal stability and insures an exceptional resistance at high temperatures. Prevent from varnish and sludge to maintain engine cleanliness.

Lower the risk of ring sticking.

Maximum protection and performance of the lubricant preserved even in the most severe conditions.

Low volatility for a reduced oil consumption and outstanding oxidation resistance of the oil to ensure extended oil drain intervals set by the carmaker.

Fulfill the most stringent performance and durability requirements through the Long Life Renault (LLR) validation test. Except for the 2.2L dCi with DPF engine, Renault RN0720 standard applies to all RENAULT vehicles fitted with Diesel

DPF engines and also to RENAULT vehicles Laguna III 1.5L dCi without DPF built before October 2008 and Kangoo II 1.5 dCi without DPF built before June 2008. When in doubt, always refer to the vehicle owner's manual.

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br\>
Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com



# **MOTUL SPECIFIC 0720 5W-30**



Lubricant for RENAULT Diesel engines with DPF Synthese-Technologie

Based on the Renault RN0720 standard, MERCEDES-BENZ MB 226.51 specification requires engine lubricants able to meet the most severe thermal constraints and being compatible with modern after treatment systems at the same time. The MB 226.51 standard applies to all Renault outsourced Diesel engines with DPF fitting MERCEDES vehicles, and requiring this standard.

The FIAT 9.55535-S4 performance level requires the lubricant to be both ACEA C4 and 5W-30, in order to perfectly lubricate Diesel engines with DPF from Renault origin fitted to FIAT vehicles and requiring this specification.

#### RECOMMENDATIONS

Drain interval: refer to manufacturer's recommendations and tune to your own use.

Do not mix with non RN0720 approved oils.

Before use always refer to the vehicle owner's manual.

# **PROPERTIES**

<u> </u>		
Viscosity grade	SAE J 300	5W-30
Density at 20°C (68°F)	ASTM D1298	0.850
Viscosity at 40°C (104°F)	ASTM D445	68.1 mm²/s
Viscosity at 100°C (212°F)	ASTM D445	11.9 mm²/s
HTHS viscosity at 150°C (302°F)	ASTM D4741	3.6 mPa.s
Viscosity Index	ASTM D2270	172.0
Pour point	ASTM D97	-36.0 °C / -33.0 °F
Sulfated Ash	ASTM D874	0.49 % weight
TBN	ASTM D2896	6.0 mg KOH/g
Flash point	ASTM D92	224.0 °C / 435.0 °F