



MOTUL STREET RIDER PEUGEOT 2T



**Oil for 2 stroke engines Scooters
Premix / Oil Injection
Developed for PEUGEOT MOTORCYCLES
Semi Synthèse**

TYPE OF USE

Specially developed by MOTUL for PEUGEOT MOTORCYCLES. Especially designed for scooters fitted with 2 stroke engines, fuel injection system or carburettor.

Suitable for lubricating systems using oil injection systems and/or premix. Compatible with catalytic converters.

All 2-Stroke scooters used daily in the city.

PERFORMANCES

STANDARDS

API TC

JASO FC

RECOMMENDATIONS

PEUGEOT MOTORCYCLES

Used in first fill and officially recommended by PEUGEOT MOTORCYCLES.

Reinforced Semi Synthèse engine oil for 2 stroke scooter engines running at high rpm and intensively.

Provides outstanding oil film resistance for anti wear protection.

Avoid deposits and ensure engine cleanliness at all levels: combustion chamber, spark plug, top of the piston, ring grooves, exhaust port, exhaust pipe...

Anti-smoke formulation.

RECOMMENDATIONS

Mixing ratio : from 2% to 4% (from 50:1 to 25:1) according to manufacturers' requirements and to be adjusted to your own use.

PROPERTIES

Color

Visual

Green

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com

motul.com



MOTUL STREET RIDER PEUGEOT 2T



**Oil for 2 stroke engines Scooters
Premix / Oil Injection
Developed for PEUGEOT MOTORCYCLES
Semi Synthese**

Density at 20°C (68°F)	ASTM D1298	0.859 mm ² /s
Viscosity at 40°C (104°F)	ASTM D445	49.1 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	8.1 mm ² /s
Viscosity Index	ASTM D2270	133.0
Pour point	ASTM D97	-23.0 °C / -9.0 °F
TBN	ASTM D2896	1.0 mg KOH/g
Flash point	ASTM D92	138.0 °C / 280.0 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.