

SUPRACO 4040

Neat Cutting Oil

DESCRIPTION

SUPRACO 4040 is a high performance neat cutting oil designed for machining operations of bas machinability ferrous metals.

SUPRACO 4040 is compatible with all metals and can be used on non-ferrous metals.

APPLICATIONS**TYPES OF OPERATIONS**

– Covers all areas of application (cutting, drilling, boring, reaming, threading, tapping, bar turning)

TYPES OF MATERIALS

– All ferrous metals from mild steel to stainless steel, refractory and special as well as non-ferrous metals

ADVANTAGES

- High Extreme Pressure properties.
- High flash point.
- Can be used for machining operations and machine-tool lubrication.
- Easily cleanable with conventional washing processes.

TECHNICAL INFORMATION

NAME	UNITS	METHOD	SUPRACO 4040
Color	-	Visual	Amber
Aspect	-		Transparent
Density at 20°C (68°F)	g/mL	ISO 12.185	0.884
Viscosity at 40°C (104°F)	mm ² /s	ASTM D445	40.0
Flash point	°C	ASTM D92	220.0
Pour point	°C	ASTM D97	-36.0
Copper Strip Corrosion	-	NTF M 07105	1b
Storage	-		in frost-free, dry place

These characteristics are given only for information and can be updated over time.

HEALTH & SAFETY

- Free from organo-chlorinated additives
- No labeling according to CLP European regulation

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.