

SUPRACO ELECTRIC 40 A

Deformation

DESCRIPTION

SUPRACO ELECTRIC 40 A is a smooth, neat oil with a low freezing point and excellent anti-corrosion properties.

APPLICATIONS

SUPRACO ELECTRIC 40 A is a neat oil used for the impregnation of induction core contactors, circuit breakers and other similar devices.

Impregnation of core induction sheets of contactors, circuit breakers and blanking of silicon (200 HBrinell).

ADVANTAGES

- Deformations of induction metal sheets due to repeated shocks are reduced.
- SUPRACO ELECTRIC 40 A can be used for degreasing and impregnation before assembly.
- Low consumption (50 mg per contactor).
- It is not sensitive to humidity and prevents scrubbing and oxidation.

TECHNICAL INFORMATION

| TECHNICAL CHARACTERISTICS | UNITS | METHOD | SUPRACO ELECTRIC 40 A |
|---------------------------|--------------------|-------------|--------------------------|
| Color | - | Visual | Amber |
| Aspect | - | | Transparent |
| Density at 20°C (68°F) | - | ISO 12185 | 0.873 |
| Viscosity at 40°C (104°F) | mm ² /s | ASTM D445 | 48.0 |
| Flash point | °C | ASTM D92 | 238 |
| Pour point | °C | ASTM D97 | -6.0 |
| Copper Strip Corrosion | - | NTF M 07105 | 1a |
| Storage | - | | in frost-free, dry place |

These characteristics are given only for information and can be updated over time.



SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.