MOTUL TECH

DATA SHEET

SUPRACO MPL 320

Getriebeöl

DESCRIPTION

SUPRACO MPL ist ein EP-Schmierstoff für alle Arten stark belasteter Getriebe mit Ausnahme von Hypoidgetrieben.

ANWENDUNGEN

– Getriebe, alle Arten von Reduzierstücken mit Ausnahme von Hypoidgetrieben
– Schneckengetriebe
– Lager und stark belastete Maschinenteile
– Hüttenmaschinen

VORTEILE

- Sehr guter Verschleißschutz (AW) und gute Druckbelastbarkeit (EP)
- Sehr hohe Oxidationsbeständigkeit
- Nicht korrosiv gegenüber NE-Metallen, vor allem Bronzelegierungen
- Hervorragendes Demulgiervermögen

TECHNICAL INFORMATION

NAME	UNITS	STANDARDS	SUPRACO MPL 320
Dichte bei 20°C	g/mL	ASTM D1298	0.893
Viskosität bei 40°C	mm²/s	ASTM D445	346.0
Viskosität bei 100°C	mm²/s	ASTM D445	26.4
Viskositätsindex	-	ASTM D2270	101.0
Flammpunkt	°C	ASTM D92	236.0
Pourpoint	°C	ASTM D97	-15.0

These characteristics are given only for information and can be updated over time.

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.

The environmental, health and safety requirements are mentioned on the safety data sheet that is available at www.quickfds.fr