

(PREVIOUSLY SUPRACO 1000 SERIES)

SUPRACUT 20 G

Neat Cutting Oil

DESCRIPTION

SUPRACUT 20 G is a chlorine and sulphur-free range of neat cutting oils designed for standard machining operations on ferrous and non-ferrous metals.

APPLICATIONS

SUPRACUT 20 G is recommended and widely used in the automotive and mechanical industries for bar-turning operations on brass and mild steels.

ADVANTAGES

- Non foaming.
- Good antiwear properties.
- High flash point.
- Very good stability.

TECHNICAL INFORMATION

NAME	UNITS	METHOD	SUPRACUT 20 G
Color	-	Visual	Light Yellow
Aspect	-		Transparent
Density at 20°C (68°F)	-	ISO 12.185	0.849
Viscosity at 40°C (104°F)	mm ² /s	ASTM D445	22.0
Flash point	°C	ASTM D92	>200
Copper Strip Corrosion	-	ASTM D130	1a
Storage	-		in frost-free, dry place

These characteristics are given only for information and can be updated over time.

HEALTH & SAFETY

- Free of organo-chlorinated additives and active sulphur
- Formulated following INRS ND 2356-227-12 recommendations
- Good dermatological behaviour



SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.