

(PREVIOUSLY SUPRACO 556 SB)

SUPRACUT 30 K

Neat Cutting Oil

DESCRIPTION

SUPRACUT 30 K is a dark neat oil, designed for threading operations by knurling deformation of mild steels and high alloyed steels.

APPLICATIONS

SUPRACUT 30 K is especially suitable for knurling operations to realise a threading with various sizes wheels on all types of steels, from the mildest one to stainless steel and highly alloyed steels on machines such as **PEE WEE - ESCOFIER - GROS**.

In some cases, there can be a risk of staining on non-ferrous metals by using **SUPRACUT 30 K**.

ADVANTAGES

- High lubricating power.
- Good extreme-pressure properties.
- High flash point.
- Good wettability.

TECHNICAL INFORMATION

NAME	UNITS	METHOD	SUPRACUT 30 K
Color	-	Visual	Black
Density at 20°C (68°F)	-	ISO 12.185	0.873
Viscosity at 40°C (104°F)	mm ² /s	ASTM D445	32.0
Flash point	°C	ASTM D92	220.0
Copper Strip Corrosion	-	ASTM D130	1b
Storage	-		in frost-free, dry place

These characteristics are given only for information and can be updated over time.

HEALTH & SAFETY

- Free from organo-chlorinated additives and active sulphur
- Formulated following INRS ND 2356-227-12 recommendations
- Good dermatological behavior



SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.