

(PREVIOUSLY SUPRACO 1000 SERIES)

SUPRACUT 45 G

Neat Cutting Oil

DESCRIPTION

SUPRACUT 45 G is a chlorine and sulphur-free neat cutting oil designed for standard machining operations on ferrous and non-ferrous metals.

APPLICATIONS

SUPRACUT G range is recommended and widely used in the automotive and mechanical industries for bar-turning operations on brass and mild steels.

SUPRACUT 45 G can also be used as a hydraulic oil for the machine tools.

ADVANTAGES

- Non foaming.
- Good antiwear properties.
- High flash point.
- Very good stability.

TECHNICAL INFORMATION

NAME	UNITS	METHOD	SUPRACUT 45 G
Color	-	Visual	Light Yellow
Aspect	-		Transparent
Density at 20°C (68°F)	-	ISO 12.185	0.880
Viscosity at 40°C (104°F)	mm ² /s	ASTM D445	45.0
Flash point	°C	ASTM D92	230.0
Copper Strip Corrosion	-	ASTM D130	1a
Storage	-		in frost-free, dry place

These characteristics are given only for information and can be updated over time.

HEALTH & SAFETY

- Free of organo-chlorinated additives and active sulphur
- Formulated following INRS ND 2356-227-12 recommendations
- Good dermatological behaviour



SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.