

**SUPRACUT EDM 03****Elektrik Deşarjı İşleme (EDM)****KULLANIM YÖNTEMİ**

**SUPRACUT EDM 03**, kaba taslaktan yüksek hassasiyetli cilalamaya kadar tüm EDM işlemeyi karşılamak için özel olarak geliştirilmiş dielektrik bir sıvıdır.

Şeffaf ve kokusuz olan **SUPRACUT EDM 03**, kullanıcılara optimum güvenlik sunan yüksek bir parlama noktasına sahiptir.

**PERFORMANS**

**SUPRACUT EDM 03** özellikle kalıpların, pres döküm kalıplarının işlenmesi için uygundur ve özellikle karmaşık profil ve boyuttaki kesme takımları için tutarlıdır.

**SUPRACUT EDM 03**, bakır ve grafit elektrotlarla yapılan cila ve süper cila işlemleri için de önerilir.

**ÖZELLİKLER**

Renk	Görsel	Saydam
20°C (68°F) derecede yoğunluk	ISO 12.185	0.818 g/mL
40°C (104°F) derecede vizkozite	ASTM D445	2.3 mm <sup>2</sup> /s
Bakır Şerit Korozyonu	ASTM D130	1 A
Görünüş		Şeffaf
Depolama		donmaz, kuru bir yerde
Alevlenme sıcaklığı	ASTM D92	103.0 °C

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

03/21

Motul TR İleri Teknoloji Otomotiv ve Endüstri Yağları Tic. A.Ş. - Küçükbakkalköy mah. Merdivenköy yolu caddesi No:12 K:6 Ataşehir - 34750 - İstanbul - +90216

570 65 00 - info@tr.motul.com -

**motul.com**