

(PREVIOUSLY SUPRACUT EVO 300 SERIES)

SUPRACUT EVO 20 M

Neat Cutting Oil

DESCRIPTION

SUPRACUT EVO 20 M is a chlorine and sulphur-free neat cutting oil designed for general machining operations of all types of metals and in all types of machines.

APPLICATIONS

SUPRACUT EVO M is a range of neat cutting oils designed for all standard turning operations of hard materials (steel, titanium and inconel), non-ferrous metals and mild steels.

SUPRACUT EVO 20 M reduces significantly the cutting force which results in very neat surfaces and it is hence also perfect for cutting operations with very small chip removal.

ADVANTAGES

- Wide range of applications.
- Chlorine and active sulphur free.
- Good anti-wear properties.
- High flash point.
- High viscosity index.

TECHNICAL INFORMATION

NAME	UNITS	METHOD	SUPRACUT EVO 20 M
Color	-	Visual	Light Yellow
Aspect	-		Clear
Density at 20°C (68°F)	-	ISO 12.185	0.841
Viscosity at 40°C (104°F)	mm ² /s	ISO 3104	22.0
Flash point	°C	ASTM D92	> 210
Copper Strip Corrosion	-	ASTM D130	1b
Storage	-		in frost-free, dry place

These characteristics are given only for information and can be updated over time.

HEALTH & SAFETY

- Free of organo-chlorinated additives and active sulphur
- Formulated with INRS ND 2356-227-12 recommendations
- Good dermatological behavior

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.