

(PREVIOUSLY SUPRACUT EVO 200 SERIES)

SUPRACUT EVO 30 G

Neat Cutting Oil

DESCRIPTION

SUPRACUT EVO 30 G is a chlorine and sulphur-free range of neat cutting oils designed for standard machining operations on ferrous and non-ferrous metals.

APPLICATIONS

SUPRACUT EVO G is a range of neat cutting oils designed for all standard machining operations on ferrous and non-ferrous metals.

SUPRACUT EVO 30 G is particularly suitable for machining operations on aluminium, brass, copper and all types of steels. Its use can be extended to some fine blanking operations as well as roller burnishing.

ADVANTAGES

- Wide range of applications.
- Chlorine and active sulphur free.
- Good anti-wear properties.
- High flash point.
- High viscosity index.

TECHNICAL INFORMATION

NAME	UNITS	METHOD	SUPRACUT EVO 30 G
Color	-	Visual	Yellow
Density at 20°C (68°F)	-	ISO 12.185	0.849
Viscosity at 40°C (104°F)	mm ² /s	ASTM D445	30.0
Flash point	°C	ASTM D92	230.0
Copper Strip Corrosion	-	ASTM D130	1b
Storage	-		in frost-free, dry place

These characteristics are given only for information and can be updated over time.

HEALTH & SAFETY

- Free from organo-chlorinated additives and active sulphur
- Formulated with INRS ND 2356-227-12 recommendations
- Good dermatological behavior



SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.