

SUPRACUT INO 20 XG

Neat Cutting Oil

DESCRIPTION

SUPRACUT INO 20 XG is a premium chlorine and sulphur-free neat cutting oil designed for all hard machining on non-ferrous and ferrous metals.

APPLICATIONS

SUPRACUT INO XG is a range of neat cutting oils best suited for machining stainless steel, titanium, hard steels, nickel alloys and hard metals.

SUPRACUT INO XG is well adapted for use at high feed rates, under heavy duty and with high-pressure spray systems.

DATA LULI WHEN

ADVANTAGES

- Consumption optimization.
- Reinforced lubricating and cooling power.
- Excellent extreme-pressure performance.
- High flash point.
- Low volatility.

TECHNICAL INFORMATION

NAME	UNITS	METHOD	SUPRACUT INO 20 XG
Color	-	ASTM D1500	Light Yellow
Density at 20°C (68°F)	-	ISO 12.185	0.843
Viscosity at 40°C (104°F)	mm²/s	ASTM D445	22.0
Flash point	°C	ASTM D92	202.0
Copper Strip Corrosion	-	ASTM D130	1a

These characteristics are given only for information and can be updated over time.

HEALTH & SAFETY

- Free from organo-chlorinated additives, zinc and heavy metals
- Formulated with INRS ND 2356-227-12 recommendations
- Good dermatological behaviour
- Storage in a frost-free and dry place



SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.

