

(PREVIOUSLY SUPRACO 1300 SERIES)

**SUPRACUT MQL 20**

Minimum Quantity Lubrication

**DESCRIPTION**

**SUPRACUT MQL 20** is a synthetic neat cutting oil developed for machining involving chips removal of ferrous and non-ferrous metals, with a micro-spray circulation system.

**APPLICATIONS**

**SUPRACUT MQL** is a range of synthetic neat cutting oils best suited for milling, cutting and tapping operations on ferrous and non-ferrous metals.

**SUPRACUT MQL 20** reduces significantly the oil consumption and has high level biodegradable content.

**ADVANTAGES**

- Minimum consumption.
- Chlorine and active sulphur free.
- Consumption optimization.
- High flash point.
- High viscosity index.

**TECHNICAL INFORMATION**

NAME	UNITS	METHOD	SUPRACUT MQL 20
Color	-	ASTM D1500	Light Yellow
Aspect	-		Transparent
Density at 20°C (68°F)	-	ISO 12.185	0.832
Viscosity at 40°C (104°F)	mm <sup>2</sup> /s	ASTM D445	22.0
Flash point	°C	ASTM D92	180.0
Copper Strip Corrosion	-	ASTM D130	1a

These characteristics are given only for information and can be updated over time.

**HEALTH & SAFETY**

- Free from organo-chlorinated additives and active sulphur
- Formulated with INRS ND 2356-227-12 recommendations
- Storage in a frost-free and dry place.



## SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.