

(PREVIOUSLY SUPRACO 1300 SERIES)

SUPRACUT MQL 30

Minimum Quantity Lubrication

DESCRIPTION

SUPRACUT MQL 30 is a synthetic neat cutting oils developed for machining involving chips removal of ferrous and non-ferrous metals, with a micro-spray circulation system.

APPLICATIONS

SUPRACUT MQL is a range of synthetic neat cutting oils best suited for milling, cutting and tapping operations on ferrous and non-ferrous metals.

SUPRACUT MQL 30 reduces significantly the oil consumption and has high level biodegradable content.

ADVANTAGES

- Minimum consumption.
- Chlorine and active sulphur free.
- Good anti-wear properties.
- High flash point.
- High viscosity index.

TECHNICAL INFORMATION

NAME	UNITS	METHOD	SUPRACUT MQL 30
Color	-	Visual	Clear
Aspect	-		Transparent
Density at 20°C (68°F)	-	ISO 12.185	0.940
Viscosity at 40°C (104°F)	mm ² /s	ASTM D445	35.0
Flash point	°C	ASTM D92	>260
Copper Strip Corrosion	-	ASTM D130	1a
Storage	-		in frost-free, dry place

These characteristics are given only for information and can be updated over time.

HEALTH & SAFETY

- Free from organo-chlorinated additives and active sulphur
- Biodegradable
- Good dermatological behavior



SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.