

(PREVIOUSLY PROFILINE 10 EP)

## SUPRAGRIND 10 X

Neat Grinding Oil

### DESCRIPTION

**SUPRAGRIND 10 X** is a neat grinding oil, specially developed for grinding of hard materials of bad machinability as well as gear grinding and sharpening of carbide and HSS tools with diamond or CBN wheels.

### APPLICATIONS

**SUPRAGRIND 10 X** can be used for all types of grinding operations and more specifically for severe grinding operations and gear grinding of bad machinability materials.

Thanks to its properties, **SUPRAGRIND 10 X** is very well adapted for workshops with a fine filtration system (filtration limit 4.5µm).

### ADVANTAGES

- Non foaming.
- Good wetting and cooling properties.
- High extreme-pressure power.
- Low consumption.
- High flash point.
- Improve surface finish.
- Prevent the smearing of wheel.

### TECHNICAL INFORMATION

TECHNICAL CHARACTERISTICS	UNITS	METHOD	SUPRAGRIND 10 X
Color	-	Visual	Light Yellow
Density at 20°C (68°F)	-	ISO 12185	0.841
Viscosity at 40°C (104°F)	mm <sup>2</sup> /s	ASTM D445	10.0
Flash point	°C	ASTM D92	145.0
Copper Strip Corrosion	-	NTF M 07105	1b
Storage	-		in frost-free, dry place

These characteristics are given only for information and can be updated over time.

### HEALTH & SAFETY

- Free of organo-chlorinated additives
- Formulated following INRS ND 2356-227-12 recommendations
- Good dermatological behaviour

**SERVICES AND EQUIPMENT**

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.