



Scooter LE 4T 10W30

**4-Stroke Scooter Engine Oil
Urban & Utility
HC-TECH® – Low Emission – JASO MB**

TYPE OF USE

All 4-stroke scooter engines for which manufacturers recommend JASO MB oils.
Suitable for all types of gasoline fuels, leaded or unleaded, biofuels.

PERFORMANCES

STANDARDS API SN
SPECIFICATION JASO MB under N° M065MOT289

Engine oil reinforced with HC-TECH® technology to provide superior protection on engine that leads to an increase in engine lifetime.

High temperature resistance particularly indicated for city use: full load during long periods and stop and go use with difficult cooling.

JASO MB lubricant ensures optimal scooter performance and fuel economy.

Provides good anti-oxidation properties to minimize the premature ageing of oil.

Effectively controls piston deposits, sludge and wear.

Low volatility for reduced oil consumption.

Ageing resistance, Anti-oxidation, Anti-corrosion, Anti-foam properties.

RECOMMENDATIONS

Drain interval: according to manufacturers' recommendations and adjusted according to particular use.

Can be mixed with synthetic or mineral oils.

MOTUL Scooter LE 4T should not be used on systems that require JASO MA specification.

PROPERTIES

Viscosity grade	SAE J 300	10W-30
Density at 20°C (68°F)	ASTM D4052	0.862
Viscosity at 40°C (104°F)	ASTM D445	69.2 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	10.3 mm ² /s
Viscosity Index	ASTM D2270	134
Pour point	ASTM D97	-42°C
Flash point	ASTM D92	226°C
TBN	ASTM D2896	6.9 mg KOH/g