



Scooter 4T 10W30

4-Stroke Scooter Engine Oil
Urban & Utility
HC-TECH® – JASO MA

TYPE OF USE

Specifically designed for scooters fitted with 4-stroke engines, any engine displacement, with or without catalytic converters, with wet clutch.

All scooters are used for daily commuting and urban riding.

Suitable for all types of gasoline fuels, leaded or unleaded, biofuels.

PERFORMANCES

STANDARDS
SPECIFICATION

API SN
JASO MA under N° M065MOT237

Engine oil reinforced with HC-TECH® technology to provide superior protection on engine.

JASO MA specification offers excellent friction levels to guarantee clutch response and durability.

Excellent high temperature resistance particularly indicated for city use: full load during long periods and stop and go use with difficult cooling.

The SAE 10W-30 viscosity grade corresponds to the most recent manufacturers' recommendations.

Low volatility for reduced oil consumption.

Ensures engine cleanliness, detergent and dispersive properties, and resistance to viscosity increase from unburned deposits produced by the engine. Ageing resistance.

Anti-oxidation, Anti-corrosion, Anti-foam properties.

RECOMMENDATIONS

Drain interval: according to manufacturers' recommendations and tune to your own use.

Can be mixed with synthetic or mineral oils.

PROPERTIES

Viscosity grade	SAE J 300	10W-30
Density at 20°C	ASTM D4052	0.864
Viscosity at 40°C	ASTM D445	75.8 mm²/s
Viscosity at 100°C	ASTM D445	11.6 mm²/s
Viscosity Index	ASTM D2270	137
Pour point	ASTM D97	-34°C
Flash point	ASTM D92	240°C
TBN	ASTM D2896	7.4 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - France. Tel : 33 1 48 11 70 00 - Fax : 33 1 48 33 28 79 - Web Site : www.motul.com

09/24