



SNOWPOWER 2T

2-Stroke Engine Lubricant for Snowmobile

Technosynthese® - Ester

TYPE OF USE

Specially formulated for snowmobile with 2 stroke engines working under the most extreme weather conditions: polar cold.

All snowmobile 2 stroke engines with injector systems or lubricated by premix.

All type of use including racing.

PERFORMANCE

STANDARDS API TC
 ISO-L-EGD

Synthetic lubricant Technosynthese® - Ester based with low pour point (-45°C / -49°F) formulated with a low content of solvent for easy start up at very low temperature.

Low ash formulation lubricant, Ester based with an effective detergent & dispersant power for a perfect piston, chamber and power valves cleanliness.

Mixes instantaneously with gasoline and remains stable.

Reduces friction and wear to increase engine life.

Anti-smoke.

RECOMMENDATIONS

Mixing ratio: from 2% to 4% (from 50:1 to 25:1) according to manufacturers' requirements and adjust according to your own use.

PROPERTIES

Color	Visual	Blue
Density at 20°C (68°F)	ASTM D4052	0.854
Viscosity at 40°C (104°F)	ASTM D445	44.6 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	7.2 mm ² /s
Viscosity Index	ASTM D2270	123
Flash point	ASTM D92	141°C / 285.8°F
Pour point	ASTM D97	-45°C / -49.0°F
TBN	ASTM D2896	1.8 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - France. Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79. Web Site: www.motul.com

02/26