

TRANSLUBE POWER 75W-90

**Lubricant for Outboard Propeller Box
100% Synthetic – Ester based**

TYPE OF USE

High Performance anti-emulsion gear oil specially formulated to lubricate outboard big engine high loaded propeller boxes : EVINRUDE, FORCE, JOHNSON, MARIMER, MERCURY, SEAGULL, SELVA, SUZUKI, TOHATSU, YAMAHA,...etc.

Specially developed for outboard big engine propeller boxes operating under shocks, heavy loads and low revolution speed, or moderate loads and high revolution speed.

Suitable also for all transmissions systems using gears, bevel gears, stepdown gears,...etc.

PERFORMANCES

STANDARDS API GL-4 / GL-5
 MIL-L 2105 D

100% Synthetic "Extreme Pressure" lubricant for efficient anti-wear protection, better resistance at high temperature and extended life time.

Formula reinforced with Ester to increase oil film resistance even in the most extreme conditions.

Very high lubricating properties to reduce friction and wear.

Viscosity grade 90 at high temperature to provide outstanding oil film resistance at high temperature and high load, and to reduce transmission noise.

Anti-corrosion, Anti-foam.

High anti-emulsion properties.

RECOMMENDATIONS

Drain period: according to manufacturers' recommendations and to be adapted to your own use.

A drain once a year is recommended in any case.

Not to be used in electrical reverse gear system.



TRANSLUBE POWER 75W-90

Lubricant for Outboard Propeller Box
100% Synthetic – Ester based

PROPERTIES

Viscosity grade	SAE J 306	75W-90
Density at 20°C (68°F)	ASTM D1298	0.891
Viscosity at 40°C (104°F)	ASTM D445	72.1 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	14.9 mm ² /s
Viscosity Index	ASTM D2270	220.0
Pour point	ASTM D97	-59.0 °C / -74.2 °F
Flash point	ASTM D92	201.0 °C / 393.8 °F