

**UNIVERSELLE 150 SC**

Deformation

**DESCRIPTION**

**UNIVERSELLE 150 SC** is a multi-purpose oil, free of organo-chlorinated additives, suitable for cold forming, tapping and lubrication of machine tool parts.

**APPLICATIONS**

**UNIVERSELLE 150 SC** is recommended for use as:

- Cold forming oil
- A lubricating oil for machine-tools compatible with heading oils

**ADVANTAGES**

- Compatible with all metals.
- High lubricating properties.
- High Extreme Pressure properties.
- Accidental leakage of **UNIVERSELLE 150 SC** into the cold heading circuit does not affect the properties and the performances of the heading fluid.

**TECHNICAL INFORMATION**

NAME	UNITS	METHOD	UNIVERSELLE 150 SC
Color	-	ASTM D1500	Yellow
Aspect	-		Transparent
Density at 20°C (68°F)	-	ISO 12185	0.899
Viscosity at 40°C (104°F)	mm <sup>2</sup> /s	ASTM D445	145.0
Flash point	°C	ASTM D92	216.0
Pour point	°C	ASTM D97	-12.0
Copper Strip Corrosion	-	NTF M 07105	1a
Storage	-		in frost-free, dry place

These characteristics are given only for information and can be updated over time.



# DATA SHEET

## SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.