

VIS 32

Ash-free lubricant for rotary compressors

DESCRIPTION

VIS 32 is a premium ash-free lubricants for the lubrication of air compressors and vacuum pumps.

APPLICATIONS

Lubrication of screw air compressors as well as vacuum pumps.

VIS 32 meets the following standards:

- DIN 51506 – VBL, VCL, VDL
- DIN 51506 – VBL, VCL, VDL
- ISO / DP 6521 (DAA, DAB, DAH, DAG).

ADVANTAGES

- Excellent anti-wear performance.
- Excellent protection against corrosion.
- Increase of draining intervals with respect to a standard lubricant.
- Reduction in the formation of varnish and deposits.
- Temperature of use: 50-130°C

TECHNICAL INFORMATION

NAME	UNITS	METHOD	VIS 32
Color	-	Visual	Clear
Density at 20°C (68°F)	g/mL	ISO 12185	0.855
Viscosity at 40°C (104°F)	mm ² /s	ISO 3104	32.0
Viscosity at 100°C (212°F)	mm ² /s	ISO 3104	5.5
Viscosity Index	-	ASTM D2270	108.0
Flash point	°C	ASTM D92	226.0
Pour point	°C	ASTM D97	-15.0
4 Ball test - Wear scar	mm	ASTM D2783	0.39
4 Ball test - Weld load	kg	ASTM D2783	126
Copper Strip Corrosion	-	ISO 2160	1B
Foam, Seq I, II, III	ml/ml	NFT 60 129	10-0/10-0/10-0

These characteristics are given only for information and can be updated over time.

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.