



AGRI TEKNO LA 10W40

Engine oil for Tractors and Farm machinery

CONSEILS D'UTILISATIONS

AGRI TEKNO LA 10W-40 is a high performance engine oil for tractors and farm machinery formulated with Technosynthese® technology.

PERFORMANCES

NORMES
ACEA E6/E9
API CJ-4

PERFORMANCES
DEUTZ DQC IV-18 LA, Mercedes-Benz Truck MB 228.51, MAN M 3477, CUMMINS CES 20086, CATERPILLAR ECF-3

Engine oil specially designed for the last generation of engines for Agriculture Machinery. Can be use in Farming equipment and Tractors running with low sulfur fuel (≤ 50 ppm) with turbo Diesel direct injection engines compliant low emissions exhaust gas, fitted with EGR System (Exhaust gas re-circulation) and/or SCR (Selected Catalyst Reduction) system and with or without DPF (Diesel Particulate Filter), working in highly severe conditions of load and service, requiring an ACEA E6 engine oil, "Low SAPS" with reduced content of Sulfated Ash ($\leq 1.0\%$), Phosphorus ($\leq 0.08\%$) and Sulfur ($\leq 0.3\%$). Can also be used as single lubricant in case of fleet composed of new & old generation engines.

RECOMMANDATIONS

Oil change: According to manufacturers' requirements and to be adjusted according to your own use.

PROPRIÉTÉS

Grade de viscosité	SAE J 300	10W40
Densité à 20°C		0.862
Viscosité à 40°C (104°F)	ASTM D445	102.8 mm ² /s



AGRI TEKNO LA 10W40

Engine oil for Tractors and Farm machinery

Viscosité à 100°C (212°F)	ASTM D445	15.0 mm²/s
Indice de viscosité	ASTM D2270	153.0
Point d'écoulement	ASTM D97	-39.0 °C / -38.0 °F
Point éclair	ASTM D92	228.0 °C / 442.0 °F