

ALTERNA 68

Premium Oil for Reciprocating Compressors

MINERAL BASE

DESCRIPTION

ALTERNA are premium ash-free lubricants for the lubrication of reciprocating air compressors and vacuum pumps.

BÉNÉFICES

- Excellent anti-wear performance
- Excellent protection against corrosion
- Increase of draining intervals with respect to a standard lubricant
- Reduction in the formation of varnish and deposits
- Excellent resistance to oxidation.

TECHNICAL INFORMATION

NAME	METHOD	ALTERNA 68
Couleur	Visuel	Clair
Densité à 20°C (68°F)	ISO 12.185	0.863 kg/L
Viscosité à 40°C (104°F)	ISO 3104	68,0 mm²/s
Viscosité à 100°C (212°F)	ISO 3104	9,1 mm²/s
Index de viscosité	ASTM D2270	109,0
Point éclair	ASTM D92	230,0 °C
Point d'écoulement	ASTM D97	-15,0 °C
4 Ball test	ASTM D2783	0.39 mm Wear scar / 126 kg Weld load
Foam, Seq I, II, III	NFT 60 129	10-0/10-0/10-0 ml/ml
Copper Stripe Corrosion	ISO 2160	1B





Creation Date: 01/2018

Revision Date: 07/2018

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.

RECOMMENDATIONS

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment.

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary. The safety data sheet of this product is available at www.motul.com