

زيت منخفض اللزوجة مخصص لنواقل الحركة الأوتوماتيكية المزودة بقوابض قفل الانزلاق
وصناديق نقل الحركة والتوجيه المعزز بالطاقة
تخليقي 100%

أنواع الاستخدام

زيت تشحيم تخليقي 100% منخفض اللزوجة وعالي الأداء مصمم خصيصاً لنواقل الحركة الأوتوماتيكية الحديثة (الوضع اليدوي، الوضع المتسلسل، التحكم الإلكتروني ...) المزودة بقوابض قفل الانزلاق أو غير المزودة به والتي تتطلب استخدام زيت ديكسون 6. يوصى به بشكل خاص للاستخدام في علب التروس الأوتوماتيكية وعلب نقل الحركة وأنظمة التوجيه المعزز بالطاقة المقدمة من شركات صناعة السيارات الأمريكية جنرال موتورز وفورد وكرايسلر ... وشركات صناعة السيارات الآسيوية هوندا وهيونداي وكيا وأسوزو ومرسيدس وميتسوبيشي ونيسان وتويوتا وغيرها ... أو شركات صناعة السيارات الأوروبية مثل فورد وأوبل ... وهو مناسب أيضاً للاستخدام في نواقل الحركة الأوتوماتيكية القديمة ومحولات عزم الدوران والتوجيه المعزز بالطاقة والأنظمة الميكانيكية والهيدروليكية حيث يتطلب الأمر استخدام زيوت ديكسون 3 اتش أو ديكسون 2 د. يرجى مراجعة دليل المالك أو كتيب السيارة دائماً قبل الاستخدام.

مستويات الاداء

يعد موتول ATF VI زيت تشحيم عالي التقنية تخليقي بنسبة 100% يتميز بأداء منخفض اللزوجة وفقاً لمتطلبات معايير ديكسون 3 وميركون. بفضل تركيبته الحصرية والمخصصة، يعزز زيت موتول ATF VI: - اقتصادية استهلاك الوقود للسيارات المجهزة بصناديق تروس أوتوماتيكية عن طريق تقليل الاحتكاك. - يحسن الزيت من استجابة نواقل الحركة الأوتوماتيكية في درجات الحرارة الباردة. - يمنح الزيت استجابة فائقة لنواقل الحركة الأوتوماتيكية: يوفر شعوراً سلساً بالنقل وتقليل تأخر وقت النقل. - يوفر أداءً مضاداً للاهتزاز لتجنب الاهتزازات على دولاب الموازنة للمحرك. - يحمي التروس التي أصبحت أكثر عدداً وصغراً وأكثر حملاً. - يطيل العمر الافتراضي، ويحسن استقرار القص في درجات الحرارة الساخنة ومقاومة الأكسدة. - يتميز الزيت بخصائص مكافحة التآكل، والتردي، كما أنه مضاد للرغوة.

التوصيات

يمكن خلطه فقط مع زيوت التشحيم المماثلة. تغيير الزيت: يتم تغيير الزيت وفقاً لتوصيات الشركة المصنعة مع اعتبار طبيعة استخدامك الخاص. يرجى مراجعة دليل المالك أو كتيب السيارة قبل الاستخدام.

المواصفات

Red	Visual	Color
0.843		(Density at 20°C (68°F
mm ² /s 30.5	ASTM D445	(Viscosity at 40°C (104°F
mm ² /s 6.1	ASTM D445	(Viscosity at 100°C (212°F
152.0	ASTM D2270	Viscosity Index

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

06/25

- MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79

MOTUL ATF VI



زيت منخفض اللزوجة مخصص لنواقل الحركة الأوتوماتيكية المزودة بقوابض قفل الانزلاق
وصناديق نقل الحركة والتوجيه المعزز بالطاقة
تخليقي 100%

C / 423.0 °F° 217.0

ASTM D92

Flash point

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

- MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79

motul.com

زيت منخفض اللزوجة مخصص لنواقل الحركة الأوتوماتيكية المزودة بقوابض قفل الانزلاق
وصناديق نقل الحركة والتوجيه المعزز بالطاقة
تخليقي 100%

OE PERFORMANCESECCNAMROFREP EO	
##08266-99964, #atf, ##08200-9009A, ##08200-9008A 08200-9008A, 08200-9009A, 08200-9016A, 08266-99964, (ATF DW-1 (except CVTs), ATF Z1 (except CVTs	ACURA
C-4	ALLISON TRANSMISSION
G 052 533, G 053 001, G 055 005, G 055 162, G 055 540, G 060 162, G 060 540	AUDI
PY112995PA	BENTLEY
0 22 83 ,516 142 0 22 83 ,##83222152426 ,##83220142516 432 0 22 83 ,249 403 0 22 83 ,248 403 0 22 83 ,114 397 83 ,720 289 2 22 83 ,514 163 2 22 83 ,426 152 2 22 83 ,807 ATF2), 83 22 2 305 397, 83 22 2 355 599, 83) 396 305 2 22 22 2 355 601, 83 22 2 413 477 (ATF7), 83 22 9 400 275, 83 22 9 407 738, 83 22 9 407 858, 83 22 9 407 859, 883 22 5 A28 F03 (ATF8), ATF 3+, ATF6, L12108	BMW
ATF PTF-1	BRILLIANCE
##68218057CA, ##68157995AB, ##68157995AA ##68218925AA, ##68218054CA, ##68218058CA ##68171869AA, 68043742AB, 68157995AA, 68157995AB, 68171866AA, 68171869AA, 68218054CA, 68218057CA, 68218058CA, 68218925AA, ATF+3, ATF+4, DEXRON VI Automatic Transmission Fluid, MS 90030-A5, MS 9602, SP IV Automatic Transmission Fluid	CHRYSLER
68043742AA, 68818925AA/AB, 8 & 9 Speed ,05127382 ATF, AW-1, AW-2, RP 9734 R7 for EAT6 transmissions	CITROËN
##68218057CA, ##68157995AB, ##68157995AA ##68218925AA, ##68218054CA, ##68218058CA ##68171869AA, 68043742AB, 68157995AA, 68157995AB, 68171866AA, 68171869AA, 68218054CA, 68218057CA, 68218058CA, 68218925AA, ATF+3, ATF+4, DEXRON VI Automatic Transmission Fluid, MS 9602, SP IV Automatic Transmission Fluid	DAIMLER
68043742AA, 68818925AA/AB, 8 & 9 Speed ,05127382 ATF, AW-1, AW-2, RP 9734 R7 for EAT6 transmissions	(DS (CAPSA
AV5 for ZF automatic gearbox with 8 and 9 speed-9.55550	FIAT
MERCON LV, MERCON ULV, WSS-M2C922-A1, WSS- (M2C949-A, XT-10-QLVC, XT-6-QSP (SP	FORD
##9986333 ,##88861004 ,##88861003 ,##9986153 GMW16444, 19256039, 88861003, 88861004, 88863400,## 88863401, 9986153, 9986333, AW-1, Dex HP, GM 1940184, GM 93165414, GM DEXRON HP ATF, GM DEXRON II D, GM DEXRON III H, GM DEXRON ULV ATF, GM DEXRON VI, GMW16444, GMW16974, WS	GENERAL MOTORS
##08266-99907 ,##08266-9904 ,##082000-9001 08200-9016A, ,08200-9008 ,08200-9005 ,082000-9001 08200-9017, 08266-9904, 08266-99907, ATF-11, ATF DW-1 (except CVTs), ATF-TYPE 3.1, ATF Z1 (except CVTs), B2618-OLE-025, Type 3.0	HONDA

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

- MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79

زيت منخفض اللزوجة مخصص لنواقل الحركة الأوتوماتيكية المزودة بقوابض قفل الانزلاق
وصناديق نقل الحركة والتوجيه المعزز بالطاقة
تخليقي 100%

##00232-1904/04500-00115, ##040000C90SG 00232-1904, 040000C90SG, 04500-00115, NWS-9638, SP4-M1, SPH-IV, SP-IV, SP-IV M, SP-IV-RR, WS	HYUNDAI
MATIC D, MATIC J, MATIC K, MATIC P, MATIC S	INFINITI
Besco ATF III, SCS, WSI	ISUZU
##02JDE 26444, 02JDE 26444, Fluid 8432	JAGUAR
NWS-9638, SP4-M1, SPH-IV, SP-IV, SP-IV M, SP-IV-RR, WS	KIA
AW-1, LR0022460, LR023288, LR023289, LV, TYK500050	LAND ROVER
##08886-02305, ##08886-02303, ATFWS-##00289 ##08886-80803, 00289-ATFWS, 08886-02303, 08886-02305, 08886-80803, ATF Type T-IV, ATF WS, JWS 3324, NWS 9638	LEXUS
M-1375.4, 231603, ##231603	MASERATI
##0000-77-122E-01, 0000-77-122E-01, ATF FZ, MERCON LV	MAZDA
A 001 989 45 03, A 001 989 68 03, A 001 989 77 03, A 001 989 78 03, MB 236.12, MB 236.14, MB 236.15 (except FE benefits), MB 236.16 (Except FE benefits), MB 236.17 (Except FE benefits), MB 236.41, P/N 0029890603	MERCEDES-BENZ
ATF-J3, ATF-MA1, ATF-PA, ATF SPH-IV, ATF SP- IV, Diamond ATF SP II, Diamond Queen ATF-PA, MZ320762, MZ320775, SP III	MITSUBISHI
999MP-MPT10P, 999MP-MTS00P, KLE24-00002, MATIC D, MATIC J, MATIC K, MATIC P, MATIC S, MATIC W	NISSAN
AW-1	OPEL
68043742AA, 68818925AA/AB, 8 & 9 Speed, 05127382 ATF, AW-1, AW-2, RP 9734 R7 for EAT6 transmissions	PEUGEOT
00 304 043 000, ##00004330400	PORSCHE
147 165 93	SAAB
G 053 001, G 060 540	SEAT
G 053 001, G 060 540	SKODA
DSIH 5M-66 Material Specification Rev 3	SSANGYONG
ATF-WS	SUBARU
MATIC S	SUZUKI
##08886-02305, ##08886-02303, ATFWS-##00289 ##08886-80803, 00289-ATFWS, 08886-02303, 08886-02305, 08886-80803, ATF FZ, ATF Type T-IV, ATF WS, JWS 3324, NWS 9638	TOYOTA
AW-1	VAUXHALL
775 256 31, 774 256 31	VOLVO
g 05, #g 052 025, G 052 533, G 053 001, G 055 005, G# 055 162, G 055 540, G 060 162, G 060 540	VW
AA01 500 001, Lifeguard 6, Lifeguard 6 Plus, Lifeguard 8, Lifeguard 9, M-1375.4, M-1375.5, M-1375.6, S671 090 255, S671 090 281, S671 090 312, TE-ML 11	ZF

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

- MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79

motul.com

MOTUL ATF VI



زيت منخفض اللزوجة مخصص لنواقل الحركة الأوتوماتيكية المزودة بقوابض قفل الانزلاق
وصناديق نقل الحركة والتوجيه المعزز بالطاقة
تخليقي 100%

PRODUCTSSTCUDORP	
ATF-0WS (except CVTs), AW-1, AW-2	AISIN
##4G4319A509/AA/S, 4G4319A509 / AA / S	AML
ATF 3292, ATF 4400, ATF 6000 SL	FUCHS
Class 1A-LV, M315	JALOS
1A	JATCO
68218925AA	MOPAR PARTS
ffl#	PENTOSIN
Tutela Transmission AS8	PETRONAS LUBRICANTS
lds, AW-1, RP 9734 R7 for EAT6 transmissions#	PSA Groupe
m, #13, L-12108, M-1375.4, M-1375.5, M-1375.6#	SHELL
##S671090312, AA01 500 ,##S671090281 ,S671090255## 001, Lifeguard 6, Lifeguard 6 Plus, Lifeguard 8, Lifeguard 9, M-1375.4, M-1375.5, M-1375.6, S671 090 255, S671 090 281, S671 090 312, TE-ML 11	ZF

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br\>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

- MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79

motul.com

06/25

