



MOTUL ATV SXS POWER 10W-50 4T

100% SYNTHETIC BASE

DESCRIPTION

ATV - All Terrain Vehicle, SxS - Side by Side, SSV – Side by Side Vehicle, and buggy fitted with 4 stroke engines, integrated gearbox or not, wet or dry clutch, engines meeting Euro 2, 3, 4 or 5 emission regulation, fitted with exhaust gas after treatment systems: catalytic converters, air injection into exhaust pipe...

Recommended for ATV, SxS, SSV and buggy used for leisure and recreation.

Suitable for all type of gasoline fuels, leaded or unleaded, with or without Ethanol, biofuels.

APPLICATIONS

100% Synthetic – Ester lubricant for improved oil film resistance at high temperatures.

Formula reinforced with Ester and anti-wear additives for improved oil film shear resistance and for increased gear protection and life time duration.

The JASO MA2 approval guarantees the efficient high friction level to secure the clutch engagement during the three riding modes: Starting, Acceleration and Constant Speed.

Optimized Phosphorus and Sulfur contents for better operating conditions of catalytic converters required to meet latest emission regulation.

SERVICES AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and monitoring of your lubricants. Please contact your technical sales representative for more information.

Important Notice

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment. The safety data sheet is available on www.motul.com.

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary.