

MOTUL AUTO COOL ESSENTIAL -25°C

Ready to use cooling liquid, anti-corrosion & antifreeze, protection -25°C / -13°F
Nitrite free / Amine free / Phosphate free / Silicate free / Borate free

TYPE OF USE

MOTUL AUTO COOL ESSENTIAL -25°C is a ready to use cooling liquid, four seasons, based on monoethyleneglycol, using organic additives.

Recommended for all liquid cooling systems: passenger cars, heavy duty, construction and agriculture vehicles, gardening, ships, stationary engines ...

PERFORMANCES

STANDARDS	AFNOR NF R 15-601
	AS Standards AS 2108
	ASTM STANDARD D3306
	BRITISH STANDARD BS 6580
	China Standards GB 29743
	Cuna Standards NC 956-16 / NC 956-18
	SAE J1034
	UNE STANDARD 26-361-88/1

Contains a bitterness agent to prevent from drinking: coolants and antifreezes have a sweet taste but are harmful.

Protects the cooling system from freezing and metallic parts from corrosion.

Provides an excellent thermal exchange and increase engine cooling efficiency.

Seals, rubber pipes and plastic parts friendly.

RECOMMENDATIONS

Ready to use, do not add any water.

Drain intervals: Refer to the manufacturers' recommendation.

Do not mix with non-organic products.

This product should not be used to protect drinking water systems against freezing.

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br\>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com



MOTUL AUTO COOL ESSENTIAL -25°C

Ready to use cooling liquid, anti-corrosion & antifreeze, protection -25°C / -13°F
Nitrite free / Amine free / Phosphate free / Silicate free / Borate free

Attention, control or drain the coolant only when the engine is cold.

Dangerous. Respect the use and handling recommendations.

PROPERTIES

Color	Visual	Green
Density at 20°C (68°F)	ASTM D5931	1.056
Pour point	ASTM D97	-27.0 °C / -17.0 °F
pH	ASTM D1287	8.5
Initial crystallization	ASTM D1177	-24.0 °C / -11.0 °F
Freezing protection		-25.0 °C / -13.0 °F
Boiling point	ASTM D1120	109.0 °C / 228.0 °F

TECHNICAL DATA SHEET

2/2

Motul

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br\>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

11/22

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com